## **Technical data sheet**

# External corner, for device installation trunking Rapid 45-2 type GA-53165

Item number: 6112610





External corner  $90^\circ$  aluminium for changing the direction of device installation trunking Rapid 45-2 GA...

### Note

For anodised device installation trunking and fittings made from aluminium, light colour differences caused by permitted scatter due to the material and process conditions cannot be avoided (according to DIN 17 611). 45 mm devices can be clicked in directly. When using PC/ABS hood fittings, there may be colour differences due to the different materials.





Aluminium

### Master data

Item number	6112610
Type	GA-AS53165RW
Description 1	External corner
Description 2	Aluminium, rigid form
Manufacturer	OBO
Dimension	53x165x175
Colour	Pure white; RAL 9010
Material	Aluminium
Smallest sales unit	1
Unit of quantity	Piece
Weight	114.2 kg
Weight unit	kg/100 pc.

# **Technical data sheet**

# External corner, for device installation trunking Rapid 45-2 type GA-53165





# Dimensions Length Width 185 mm Height 53 mm 175 15

_			
т.	ahn	امما	data
16	CHIL	ıcaı	uata

Number of covers  Version for Base and cover for duct width 165 mm for trunking height 53 mm Halogen-free yes Cable retaining clip no Duct connector no Cover mounting type Internal Mounting perforation in base Cover width 45 mm Cover width 2 45 mm Protective film IP30 Protective film yes
for duct width for trunking height for trunkin
for trunking height 53 mm Halogen-free yes Cable retaining clip no Duct connector no Cover mounting type Internal Mounting perforation in base Cover width 45 mm Cover width 2 45 mm Protection rating IP30
Halogen-free yes Cable retaining clip no Duct connector no Cover mounting type Internal Mounting perforation in base Cover width 45 mm Cover width 2 45 mm Protection rating IP30
Cable retaining clip no Duct connector no Cover mounting type Internal Mounting perforation in base no Cover width 45 mm Cover width 2 45 mm Protection rating IP30
Duct connector no  Cover mounting type Internal  Mounting perforation in base no  Cover width 45 mm  Cover width 2 45 mm  Protection rating IP30
Cover mounting type Internal Mounting perforation in base no Cover width 45 mm Cover width 2 45 mm Protection rating IP30
Mounting perforation in base no Cover width 45 mm Cover width 2 45 mm Protection rating IP30
Cover width 45 mm  Cover width 2 45 mm  Protection rating IP30
Cover width 2 45 mm Protection rating IP30
Protection rating IP30
Protective film yes
Protection rating IK code IK10
Symmetrical yes
Permitted temperature range, max. 60 °C
Permitted temperature range, min15 °C
Angle range, min. 90 mm